

DELABIE



COMFORT
WATER SAVINGS
VANDAL-RESISTANT
SAFETY



TEMPOMIX

Time flow basin mixer

- ▶ Soft-touch operation
- ▶ Time flow 7 seconds
- ▶ Flow rate 3 lpm at 3 bar
- ▶ Solid brass body and reinforced fixings
- ▶ Maximum temperature limiter



More information at delabie.co.uk



Faucets

Tel: (01495) 767600

Email: sales@faucets.co.uk

Prices are excluding VAT

Commercial controls - Basins



TEMPOMATIC 4

Electronic basin mixer/tap with integrated 6V Lithium batteries.

- Reduced-stagnation solenoid valve and electronic unit built into body
- Scale-resistant flow straightener pre-set at 3 lpm at 3 bar
- Duty flush (~60 seconds every 24 hours after last use)
- Active, infrared presence detection
- Chrome-plated solid brass body with reinforced fixing
- PEX flexibles with filters and non-return valves
- Anti-blocking security

Deck-mtd mixer Ø 15mm	49000615	£338.00
Deck-mtd tap Ø 15mm	44000615	£305.00
Wall-mtd tap L. 125 F3/8"	443406	£298.00
Wall-mtd tap L. 190 F3/8"	443506	£332.00



BINOPTIC

Electronic mixer or tap with infrared presence detection.

- Flow rate pre-set at 3 lpm at 3 bar
- PEX flexibles with filters and Ø 15mm solenoid valves
- Chrome-plated brass body with reinforced fixing
- Anti-blocking security and temperature limiter
- Duty flush (~60 seconds every 24 hours after the last use)
- Independent IP65 electronic control unit and shock-resistant sensor

Deck-mtd mixer	378MCH15	£447.67
Deck-mtd tap	37801515	£337.20
Wall-mtd tap	379DER15	£345.00
Recessed tap	379ENC15	£353.97



TEMPOMIX 3

Soft-touch single control mixer.

- Time flow pre-set at ~7 seconds, can be adjusted 3-10 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 to 6 lpm
- Chrome-plated solid brass body
- Filters and non-return valves
- Adjustable maximum temperature limiter

Ø 15mm	79400015	£218.33
F3/8"	794000	£211.65




TEMPOSOFT MIX 2

Soft-touch time flow mixer.

- Time flow pre-set at ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Tamperproof scale-resistant flow straightener
- Chrome-plated solid brass body
- Maximum temperature limiter

Ø 15mm	74250015	£160.44
--------	-----------------	----------------



TEMPOSOFT 2

Deck-mounted soft-touch time flow tap.

- Time flow ~7 seconds.
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Tamperproof scale-resistant flow straightener
- Chrome-plated solid brass body M1/2"

Stocked*

M1/2"	740500*	£68.37
-------	----------------	---------------




TEMPOSOFT 2

Wall-mounted soft-touch time flow tap.

- Time flow ~7 seconds.
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Tamperproof scale-resistant flow straightener
- Chrome-plated solid brass body M1/2"

L. 110mm	741500	£67.13
L. 150mm	741550	£80.88



TEMPOMIX

Deck-mounted soft-touch time flow mixer.

- Soft-touch operation
- Temperature control and operation via the push-button
- Time flow 7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated solid brass body
- Maximum temperature limiter

Stocked*

Ø 15mm	79500015*	£210.00
--------	------------------	----------------



TEMPOSTOP

Deck-mounted time flow tap.

- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated solid brass body with spout H. 35mm, L. 110mm
- Tamperproof, scale-resistant flow straightener

M1/2"	745100	£60.76
M1/2", reinf. fixing	745300	£70.60
M1/2", anti-blocking	745301	£74.18
M1/2" lever-op	745440	£83.06



Commercial controls - Showers

**SECURITHERM shower panel**

Electronic shower panel with individual thermostatic mixer.

- 6V Battery-operated infrared sensor
- Pre-set maximum temperature limiter
- Anti-scalding failsafe: immediate shut-off if cold water supply fails
- Thermal shocks can be carried out
- Shuts off voluntarily or automatically after ~60 sec.
- Tamperproof chrome-plated ROUND shower head, scale-resistant nozzle
- Flow rate 6 lpm at 3 bar
- Ø15mm stopcocks for CF with filters and non-return valves

With top inlets	79240015	£846.14
-----------------	-----------------	----------------

**SECURITHERM shower panel**

Time flow shower panel with individual thermostatic mixer.

- Pre-set maximum temperature limiter
- Anti-scalding failsafe: immediate shut-off if cold water supply fails
- Thermal shocks can be carried out
- Time flow ~30 seconds
- Soft-touch operation
- Tamperproof chrome-plated ROUND shower head, scale-resistant nozzle
- Flow rate 6 lpm at 3 bar
- Top inlet
- Ø15mm stopcocks for CF with filters and non-return valves
- Concealed fixings

With top inlets	79230015	£690.41
-----------------	-----------------	----------------

**TEMPOMIX shower panel**

Time flow shower panel in powder-coated aluminium.

- Time flow ~30 seconds
- Soft-touch operation
- Tamperproof chrome-plated ROUND shower head, scale-resistant nozzle
- Flow rate 6 lpm at 3 bar
- Top inlet
- Ø 15mm stopcocks for CF with filters and non-return valves
- Concealed fixings

With top inlets	79030015	£586.56
-----------------	-----------------	----------------

**SPORTING 2**

Time flow shower panel in anodised aluminium.

- Adjustable connector for top or back inlets
- Slimline structure with concealed fixings
- Chrome-plated satin finish
- Soft-touch operation
- Time flow ~30 seconds
- Tamperproof fixed shower head with scale-resistant nozzle
- Flow rate 6 lpm at 3 bar
- Filter and non-return valve are accessible
- Built-in stopcock
- M $\frac{1}{2}$ " connection for mixed water supply

Stocked*


With top/back inlet	714700*	£198.61
---------------------	----------------	----------------

**TEMPOMIX 3**

Time flow shower kit in a waterproof recessing housing.

- Time flow ~30 seconds with soft-touch operation
- Tamperproof ROUND shower head with scale-resistant nozzle
- Flow rate 6 lpm at 3 bar
- Chrome-plated metal wall plate 160 x 160mm
- Waterproof housing for all installation types

Shower kit with top inlet	794BOX1 + 794219	£245.07 £209.42
Shower mixer with top inlet	794BOX1 + 794218	£245.07 £169.32

**TEMPOSTOP**

Cross wall time flow shower kit.

- Time flow ~15 or 30 seconds
- Vandal resistant cross wall control
- Tamperproof ROUND shower head with scale-resistant nozzle
- Flow rate 6 lpm at 3 bar
- Chrome-plated solid brass body
- Concealed fixing and anti-rotating nut


For walls ≤ 150mm	749159	£233.87
For walls ≤ 200mm, AB	747214	£227.14

**TEMPOGENOU**

Knee-operated time flow valve for hands-free operation.

- Time flow ~7 seconds and pre-set flow rate 3 lpm
- Control lever reinforced by stainless steel rod
- Wall plate mounted via 4 stainless steel screws
- Cold or mixed water supply

MM $\frac{1}{2}$ ", inline	73544715	£121.58
MM $\frac{1}{2}$ ", angled	734100	£95.64


**Deck-mounted spout**

Fixed cast brass spout for hands-free operation.

- Spout L. 140mm, H. 120mm, M $\frac{1}{2}$ "
- Reinforced fixing by 3 stainless steel screws
- Chrome-plated solid brass
- Flow straightener regulated at 3 lpm

Deck-mounted	981142	£78.54
--------------	---------------	---------------

Commercial controls - WCs



TEMPOMATIC

Mains supply electronic cross wall valve for direct flush.

- IP65 independent electronic unit
- Mains supply with 1" solenoid valve
- Voluntary or automatic flush
- Time flow ~7 seconds, can be adjusted from 3-12 seconds.
- Detection distance, flow rate and flush volume are adjustable
- Stopcock FF1"
- Threaded rod can be cut to size

For walls ≤ 30mm	463030	£767.02
For walls ≤ 160mm	463150	£767.02
For walls ≤ 225mm	463200	£772.90



TEMPOMATIC dual control

Electronic direct flush valve in a waterproof housing.

- Satin finish stainless steel wall plate 186 × 186mm
- Voluntary flush via push-button (anti-blocking function) or automatically when user leaves
- Intelligent flush volume adapts according to use
- Waterproof housing for all installation types
- F¾" flush valve
- Integrated vacuum breaker, stopcock and flow rate/flush volume adjuster

6V battery	464PBOX + 464006	£135.68 £429.66
Mains	464SBOX + 464000	£135.68 £452.26




TEMPOFLUX 3

Time flow direct flush valve in a waterproof housing.

- Satin finish stainless steel wall plate 210 × 162mm
- Dual flush 3L/6L, can be adjusted to 2L/4L
- Compatible with wall finishes 10-120mm
- Waterproof housing for all installation types
- F¾" flush valve is compatible with sea water and grey water
- Integrated vacuum breaker, stopcock and flow rate/flush volume adjuster

3L/6L recessed	763BOX + 763000	£113.08 £135.68
----------------	------------------------	----------------------------------



TEMPOFLUX 1

Cross wall time flow flush kit.

- Cross wall control, can be cut to size
- Soft-touch operation
- Inlet M¾" with integrated stopcock and flow rate/flush volume adjuster
- Integrated vacuum breaker
- Connection washer Ø 32/55mm

≤ 150mm, with flush tube	761700	£215.56
≤ 200mm, without flush tube	761200	£184.51

Commercial controls - Urinals



TEMPOMATIC 4

Exposed electronic urinal valve, 6V Lithium battery.

- Reduced-stagnation solenoid valve and electronic unit built into the body of the valve
- 3 rinsing programmes
- High-frequency mode (exclusive to DELABIE)
- Hygienic duty flush (every 24 hours after last use)
- Flow rate 0.25 L/sec at 3 bar
- Built-in stopcock and flow rate adjuster
- One-piece chrome-plated metal body M½"

Inline	479406	£340.34
Angled	479408	£303.84
Angled, flush tube Ø 35mm	479407	£328.17



TEMPOMATIC 4

Recessed electronic urinal valve, 6V Lithium battery.

- Mains supply or battery operated
- Stainless steel wall plate 145 × 145mm with integrated electronics
- 3 rinsing programmes
- High frequency mode (exclusive to DELABIE)
- Hygienic duty flush every 12 or 24 hours (or off)
- Waterproof housing, for all installation types
- Other finishes available: black glass, satin and white powder-coated

Polished st. steel 6V battery	430PBOX + 430016	£109.82 £322.44
Polished st. steel Mains	430SBOX + 430010	£122.53 £344.64




TEMPOFLUX

Recessed time flow urinal valve in a waterproof housing.

- Satin finish stainless steel wall plate 145 × 145mm
- Flow rate 0.15 l/sec at 3 bar, can be adjusted
- Time flow 3 seconds with soft-touch operation
- Compatible with wall finishes 10 - 120mm
- Waterproof housing for all installation types
- F½" flush valve is compatible with sea water and grey water
- Integrated stopcock and flow rate adjuster

Satin stainless steel	778BOX + 778700	£104.45 £152.65
-----------------------	------------------------	----------------------------------



TEMPOSOFT 2

Individual time flow urinal valve M½".

- Soft-touch operation
- Time flow ~3 seconds
- Flow rate pre-set at 0.15 l/sec at 3 bar, adjustable
- Chrome-plated solid brass body M½"

Inline	777800	£67.04
Angled	778800	£62.00



Frame systems

**TEMPOFIX 3 with TEMPOMATIC 4 urinal**

Frame system W. 430mm for wall-hung electronic urinals.

- Black powder-coated steel frame system with wall fixings
- Fixes to floor and load-bearing walls
- Frame height can be adjusted
- Bracket can be adjusted 100-280mm
- For walls up to 120mm
- Fitted with TEMPOMATIC 4 electronic direct flush valve F $\frac{1}{2}$ "
- 230/6V mains supply

Battery-operated versions also available

Bright stainless steel finish	543000 + 430010	£385.53 £344.64
Satin stainless steel finish	543000 + 430000	£385.53 £344.64

**TEMPOFIX 3 with TEMPOFLUX urinal**

Frame system W. 430mm for wall-hung time flow urinals.

- Black powder-coated steel frame system with wall fixings
- Fixes to floor and load-bearing walls
- Frame height can be adjusted
- Bracket can be adjusted 100-280mm
- For walls up to 120mm
- Fitted with TEMPOFLUX F $\frac{1}{2}$ " time flow flush valve
- Time flow ~3 seconds

For urinals Ø 35mm	543006 + 778700	£373.86 £152.65
For urinals with flexible $\frac{1}{2}$ "	543006D + 778700	£373.86 £152.65

**TEMPOFIX 3 with TEMPOMATIC dual control WC**

Frame system W. 350mm for wall-hung electronic WCs.

- Black powder-coated self-supporting steel frame system (or wall-mounted model)
- Fixes to load-bearing floors via metal rawl plugs
- Frame height can be adjusted from 0 - 200mm (with 1m mark)
- Ø110mm soil pipe
- Complies with French standard NF D12-208
- Fitted with TEMPOMATIC dual control direct flush valve F $\frac{3}{4}$ "

Battery-operated versions also available

Self-supporting model, mains	564005DE + 464000	£361.81 £452.26
Wall-mounted model, mains	564000DE + 464000	£344.86 £452.26

**TEMPOFIX 3 with TEMPOFLUX 3 WC AB**

Frame system W. 350mm for wall-hung time flow WCs.

- Black powder-coated self-supporting steel frame system
- Fixes to load-bearing floors via metal rawl plugs
- Frame height can be adjusted from 0 - 200mm (with 1m mark)
- Ø110mm soil pipe
- Complies with French standard NF D12-208
- Fitted with TEMPOFLUX 3 F $\frac{3}{4}$ " time flow direct flush valve

Self-supporting model	564065DE + 763000	£361.81 £135.68
Self-supporting model	564060DE + 763000	£344.86 £135.68

Additional Fittings

**PREMIX NANO**

Thermostatic mixing valve for mixed water distribution.

- For 1-2 taps or 1 shower
- Anti-scalding failsafe: immediate shut-off if hot or cold water supply fails
- Temperature pre-set at 38°C, can be adjusted by installer 34-60°C
- Filters and non-return valves
- Minimum operational flow-rate: 3 lpm
- Thermal shocks can be carried out
- Inlets and outlet Ø15mm

Stocked*

M $\frac{1}{2}$ " 15mm, chrome	732116*	£82.84
M $\frac{1}{2}$ " 15mm, nickel	732115	£70.40

**PREMIX COMFORT**

Group thermostatic mixing valve for mixed water distribution.

- Anti-scalding safety: maximum temperature limiter
- Temperature pre-set at 38°C, can be adjusted from 32 - 42°C
- Thermal shocks are possible
- Integrated filters and non-return valves can be accessed externally
- For up to 40 points-of-use, flow rate 55 - 190 lpm at 3 bar

$\frac{3}{4}$ ", 55 lpm	731002	£474.32
1", 90 lpm	731003	£735.19
1 $\frac{1}{4}$ ", 140 lpm	731004	£1,055.36
1 $\frac{1}{2}$ ", 190 lpm	731005	£1,363.66

**Adjustable height floor trap**

Floor trap for soft or vinyl floors with adjustable height.

- Flow rate 36 lpm, outlet Ø43mm
- Water level 50mm
- Bright polished stainless steel grid Ø 114mm
- Integrated plate to seal waterproof membrane
- Height adjusts up to 85mm with extension

Stocked*

Outlet Ø 43 mm	683002UK*	£58.32
----------------	-----------	---------------

**BIOSAFE spout outlet**

Hygienic spout outlet for mixers and taps.

- Free flow outlet with no grid or partitions in contact with the water
- Water cannot stagnate in the internal part
- Scale-resistant Hostaform® interior
- Chrome-plated brass collar
- Flow rate must be limited to ensure a smooth, laminar flow

M24/100	923024	£6.08
F22/100	923022	£6.08

Hospital



Sequential Securitouch mechanical mixer

Sequential mechanical 90° mixer, smooth interior.

- Progressive temperature control, open and closing on cold water
- Securitouch thermal insulation prevents burns
- Flat swivelling under spout L. 200mm with hygienic flow straightener
- Pre-set temperature limiter
- Smooth interior and low water volume
- Flow rate limited to 6 lpm at 3 bar
- Hygiene control lever L. 200mm

150mm centres, inline SC	2436P	£314.32
--------------------------	--------------	----------------



SECURITHERM EP Securitouch mixer

Pressure-balancing mixer, smooth interior.

- Anti-scalding safety: HW flow rate reduced if CW supply fails
- Securitouch thermal insulation prevents burns
- Flat swivelling under spout L. 200mm with hygienic flow straightener
- Pre-set temperature limiter
- Smooth interior and low water volume
- Flow rate limited to 5 lpm at 3 bar
- Available without Pressure Balancing (EP)

EP, 150mm, inline SC	2446LEPUK	£348.02
EP, 200mm, inline SC	2447LEPUK	£384.43
200mm, inline SC	2447LUK	£330.38



Mechanical mixer BIOCLIP spout

Mixer with BIOCLIP removable spout and Hygiene lever.

- BIOCLIP spout can be removed for cleaning and disinfection
- Ceramic cartridge Ø 40mm with maximum temperature limiter
- Smooth body and spout interiors
- Flow rate limited to 5 lpm at 3 bar
- Suitable for BIOFIL spout filters
- Also available with disposable Hostaform® spouts

Spout H. 160	2870T1	£304.57
Spout H. 300	2870T3	£328.64




BIOSAFE mechanical mixer

Mixer with no spout and very low water volume in the body.

- BIOSAFE hygienic spout outlet integrated into the body
- Smooth interior and very low water volume
- Flow rate limited to 4 lpm at 3 bar
- Thermal shocks are possible without removing the control lever
- Available with Pressure Balancing (EP)
- Copper tails

With pop-up waste	26206	£214.83
No pop-up waste	26216	£192.21
EP, with pop-up waste	26206EP	£248.75
EP, no pop-up waste	26216EP	£226.13




SECURITHERM sequential mixer

Sequential thermostatic mixer.

- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves on the inlets
- Smooth interior slows bacterial development

15mm, lever L. 146	H960015	£302.00
15mm, lever L. 100	H960015L	£300.00
Coppertails, lever L. 146	H9600610	£330.00
Coppertails, lever L. 100	H9600610L	£328.00



SECURITHERM BIOCLIP sequential mixer

Removable sequential thermostatic BIOCLIP mixer.

- Mixer can be easily removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves on the inlets
- Smooth interior slows bacterial development

Stocked*

15mm, lever L. 146	H960515	£342.00
15mm, lever L. 100	H960515L	£340.00
Coppertails, lever L. 146	H9605610*	£370.00
Coppertails, lever L. 100	H9605610L	£368.00



Wall-mtd SECURITHERM sequential BIOCLIP mixer

Sequential thermostatic mixer with BIOCLIP spout.

- BIOCLIP spout can be removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves on the inlets
- Smooth interior slows bacterial development

Stocked*

150mm, inline SC	H9611P	£438.69
200mm, inline SC	H9614P*	£437.90



Pillar-mtd SECURITHERM sequential BIOCLIP mixer

Sequential thermostatic mixer with BIOCLIP spout.

- BIOCLIP spout can be removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves on the inlets
- Smooth interior slows bacterial development

200mm, pillar	H9615	£499.01
---------------	--------------	----------------



Hospital

**BIOFIL cartridge filter**

Single use BIOFIL cartridge with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Laminar flow
- Maximum lifespan 62 days for both non-sterile and sterile filter
- 10 cartridges individually wrapped

Sterile	20051A.10P	£719.06
Sterile	20051P.10P	£719.06
Non-sterile	30051A.10P	£574.09
Non-sterile	30051P.10P	£574.09
Connector 'A' F22/100	820022	£22.62
Connector 'A' M24/100	820024	£22.62
Connector 'P' F22/100	820122	£28.27
Connector 'P' M24/100	820124	£28.27

**BIOFIL shower head filter**

Single use BIOFIL shower head with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Maximum lifespan 62 days for both non-sterile and sterile filter
- 10 shower heads individually wrapped

Sterile threaded	20061.10P	£902.54
Sterile push-fit	20060.10P	£902.54
Non-sterile threaded	30061.10P	£757.30
Non-sterile push-fit	30060.10P	£757.30

**BIOFIL spout filter**

Single use BIOFIL spout with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Maximum lifespan 62 days for both non-sterile and sterile filter
- 10 spouts individually wrapped

Sterile	20040.10P	£743.85
Non-sterile	30040.10P	£732.86

**BIOCLIP spouts**

Removable BIOCLIP spouts in stainless steel and Hostaform®.

- For use with BIOCLIP mixers/taps
- Removable stainless steel spouts Ø 28mm with hygienic flow straightener suitable for BIOFIL terminal filters. Available in two lengths, 129mm and 77mm
- Removable, disposable Hostaform® spouts Ø 22mm with star-shaped flow straightener. Length 125mm. Individually wrapped

2 x St. steel, L. 129	20002	£82.61
2 x St. steel, L. 77	20003	£77.81
15 x Hostaform®, L. 125	20015	£76.17

**SECURITHERM Securitouch sequential shower**

Sequential thermostatic shower mixer.

- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Progressive temperature control from cold water to 39°C
- Securitouch thermal insulation prevents burns
- Maximum temperature limiter
- Smooth interior slows bacterial development
- Flow rate regulated at 9 lpm
- Supplied with in-line STOP/CHECK connectors, 150mm centres

M½" bottom outlet	H963015	£296.01
M¾" top outlet	H964015	£296.01

**SECURITHERM Securitouch shower**

Dual control thermostatic shower mixer.

- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Securitouch thermal insulation prevents burns
- Adjustable temperature 25 - 41°C with maximum temperature limiter
- M½" shower outlet
- Supplied with in-line STOP/CHECK connectors, 150mm centres, with filters and non-return valves

M½"	H9741TP	£282.00
-----	---------	---------

**SECURITHERM sequential recessed shower**

Sequential thermostatic shower mixer in a waterproof housing.

- Sequential shower mixer with polished stainless steel wall plate
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Securitouch thermal insulation prevents burns
- Maximum temperature limiter
- Flow rate regulated at 9 lpm
- Waterproof recessing housing

Stocked*

SECURITHERM shower	H9632*	£305.00
Waterproof housing	790BOX*	£82.82

**SECURITHERM EP Securitouch shower**

Pressure-balancing shower mixer.

- Anti-scalding safety: HW flow rate reduced if CW supply fails
- Securitouch thermal insulation prevents burns
- EP pressure-balancing ceramic cartridge Ø 40mm with maximum temperature limiter
- M½" shower outlet
- Flow rate regulated at 9 lpm
- Supplied with M½" M¾" offset STOP/CHECK connectors with filters and non-return valves

With STOP/CHECK connectors	2739EP	£256.96
----------------------------	--------	---------

Accessibility & Independence



DOC M recessed shower pack

DOC M compliant white powder-coated shower pack.

- 2 x drop-down support rails, 3 x 600mm grab bars, 2 x 450mm grab bars
- Lift-up shower seat with backrest
- 2 x white PVC shower curtain and rail
- SECURITHERM thermostatic recessed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and wall outlet
- Stainless steel coat hook

White powder-coated | **DOCMREC1** | **£1,690.00**



DOC M recessed shower pack

DOC M compliant blue powder-coated shower pack.

- 2 x drop-down support rails, 3 x 600mm grab bars, 2 x 450mm grab bars
- Lift-up shower seat with backrest
- 2 x white PVC shower curtain and rail
- SECURITHERM thermostatic recessed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and wall outlet
- Stainless steel coat hook

Blue powder-coated | **DOCMREC2** | **£1,690.00**



DOC M exposed shower pack

DOC M compliant white powder-coated shower pack.

- 2 x drop-down support rails, 3 x 600mm grab bars, 2 x 450mm grab bars
- Lift-up shower seat with backrest
- 2 x white PVC shower curtain and rail
- SECURITHERM thermostatic exposed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and 1.0m riser pipe
- Stainless steel coat hook

White powder-coated | **DOCMEXP1** | **£1,533.35**



DOC M exposed shower pack

DOC M compliant blue powder-coated shower pack.

- 2 x drop-down support rails, 3 x 600mm grab bars, 2 x 450mm grab bars
- Lift-up shower seat with backrest
- 2 x white PVC shower curtain and rail
- SECURITHERM thermostatic exposed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and 1.0m riser pipe
- Stainless steel coat hook

Blue powder-coated | **DOCMEXP2** | **£1,533.35**

Hygienic Accessories



Toilet paper dispenser

Large paper dispenser.

- One-piece hinged cover for easy maintenance and better hygiene
- With lock and standard DELABIE key
- With back piece: protects the paper from wall imperfections, damp and dust
- Model for 400m rolls; also available for 200m rolls
- Dimensions: Ø 305mm, depth 135mm

Bright polished st steel	2911	£134.17
Polished satin st steel	2912	£134.17
White lacquered steel	2910	£73.63



HIGHFLOW hand dryer

Compact air pulse hand dryer.

- Bacteriostatic 304 stainless steel
- Robust model
- High speed: dries in 10 - 12 seconds
- Choice of warm or cold air
- Anti-blocking
- Dimensions: 175 x 238 x 267mm
- 3-year warranty. CE marked

Bright polished st steel	510622	£393.64
Polished satin st steel	510622S	£393.64
White lacquered steel	510622W	£393.64



Electronic soap dispenser

Electronic liquid soap dispenser.

- Bacteriostatic 304 stainless steel
- Vandal-resistant model with lock and standard DELABIE key
- Non-touch, no waste pump dispenser, 0.8ml. dose
- One-piece hinged cover for better hygiene
- Power supply: 6 AA batteries supplied
- Low battery indicator light
- Easy-to-fill tank, capacity 1 litre
- For vegetable-based liquid soap (up to 3,000 mPa.s)

Bright polished st steel	512066P	£170.48
Polished satin st steel	512066S	£170.48
White powder-coated	512066W	£170.48



Liquid soap dispenser

Liquid soap dispenser with soft-touch operation.

- Bacteriostatic 304 stainless steel
- One-piece hinged cover for easy maintenance and better hygiene
- Anti-blocking system and no-waste pump dispenser
- With lock and standard DELABIE key
- Easy-to-fill tank
- For vegetable-based liquid soap (up to 3,000 mPa.s)

1L, bright polished	510580	£93.22
1L, polished satin	510582	£87.30
1L, white	510581	£82.46
0.5L, bright polished	510583	£87.63
0.5L, polished satin	510586	£82.05
0.5L, white	510584	£77.52



Sanitary Ware

**ALGUI washbasin**

Countertop stainless steel washbasin.

- Suitable for use with wall-mounted or extended mixers/taps
- Basin internal diameter 310mm
- Bacteriostatic 304 stainless steel
- Dual finish: polished interior, satin exterior
- Supplied with 1½" waste, no overflow
- Complies with EN 14688
- Weight: 3.8kg

Polished satin st steel	120110	£421.45
Dual finish	120112	£504.16

**BOB washbasin**

Wall-mounted stainless steel washbasin, concealed drainage.

- Basin internal diameter 310mm
- Bacteriostatic 304 stainless steel
- Polished satin finish
- Rounded edges prevent injury
- Vandal-resistant shrouded basin, concealed trap
- Supplied with 1½" waste and trap, no overflow
- Complies with EN 14688
- Weight: 5.5kg

Without tap hole	120130	£287.08
------------------	---------------	----------------

**CANAL wash trough**

Wall-mounted stainless steel wash trough for 1 - 5 services.

- Bacteriostatic 304 stainless steel
- Polished satin finish
- Light weight, easy to install (no joint concealers)
- Supplied with brackets and fixing elements
- Complies with EN 14296

L. 600, 1 service	120240	£337.05
L. 1,200, 2 services	120250	£383.16
L. 1,200, with tap hole	121250	£383.16
L. 1,400, 2-3 services	120260	£423.49
L. 1,800, 3-4 services	120280	£466.71
L. 2,400, 4 services	120300	£580.55
L. 3,000, 5 services	120310	£640.10

**SXS electronic hand washbasin**

Wall-mtd stainless steel hand washbasin with electronic control.

- Bacteriostatic 304 stainless steel
- Rounded edges prevent injuries
- Supplied with a WRAS approved electronic tap, TMV3 and WRAS approved thermostatic mixing valve and soap dispenser
- Water savings: flow rate pre-set at 3 lpm
- Maximum hygiene: no manual contact with tap
- Weight: 4.1kg

Without splashback	18431015	£705.68
With splashback	18432015	£743.71

**S21 and 700 WC pans**

Wall-hung or floor-standing stainless steel WC pans.

- Bacteriostatic 304 stainless steel
- Polished satin finish
- One-piece pressed bowl with no seams
- Concealed perimetral flushing rim
- Horizontal inlet Ø 55mm; horizontal waste Ø 100mm. Supplied with PVC pipe
- Easy to install

S21 S wall-hung	110310	£725.92
S21 P floor-mtd	110300	£763.44
700 S wall-hung	110710	£893.08
700 P floor-mtd	110700	£931.49

**FINO urinal**

Wall-hung stainless steel rimless urinal.

- Bacteriostatic 304 stainless steel
- Quick and easy to install from the front thanks to a stainless steel mounting frame
- Polished satin finish
- Recessed or exposed water inlet
- Recessed or exposed water outlet
- Supplied with 1½" P trap and fixing elements
- Complies with EN13407
- Weight: 3.5kg

Recessed water inlet	135710	£331.41
Exposed water inlet	135110	£331.41

**EASY-D ceramic urinal pack**

Ceramic "all-in-one" solution.

- EASY-D ceramic urinal packs contain:
- A ceramic rimless urinal with concealed trap
 - A TEMPOSOF 2 exposed time flow urinal valve: soft-touch operation, time flow ~3 seconds
 - Neck tube, water nozzle, waste, trap and fixing elements kit

Pack with angled valve	133888	£253.43
Pack with in-line valve	133788	£253.43
Urinal only Recessed inlet	134718	£175.46
Urinal only Exposed inlet	134118	£175.46

**Trough urinal**

Wall-hung stainless steel trough urinal.

- Bacteriostatic 304 stainless steel
- Polished satin finish
- Top inlet F½" and sparge pipe for rinsing
- 1½" waste outlet, drains on the right side
- Weight: 1,200mm model is 17.5kg, 1,800mm model is 24.8kg, 2,400mm model is 32.1kg
- Stall waste with integrated trap included

L. 1,200mm	130100	£590.00
L. 1,800mm	130110	£790.00
L. 2,400mm	130120	£950.00

Safety Controls



Free-standing eye wash and shower combination

Free-standing safety eye wash and shower with large flow rates.

- Frost-free system as standard
- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- Circular shower head Ø 250mm, flow rate 70 lpm at 1 bar (120 lpm at 3 bar)
- Water supply F1"
- Galvanised steel pipes, green powder-coated controls

Combination	9203	£842.85
-------------	------	---------



Wall-mounted safety shower

Wall-mounted recessed safety shower with manual control.

- Frost-free system as standard
- Circular shower head Ø 250mm, flow rate 70 lpm at 1 bar (120 lpm at 3 bar)
- ¼-turn valve, flow activated by triangular handle
- Water supply F1"
- Galvanised steel pipes, green powder-coated shower head and pull handle

Shower	9108	£173.70
--------	------	---------



Wall-mounted eye wash station

Wall-mounted eye wash station with manual control.

- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- ¼-turn valve, flow activated by hand control
- Water supply M½"
- Galvanised steel pipes, green powder-coated basin and control

Wall-mounted	9102	£354.13
--------------	------	---------



Free-standing eye wash station

Free-standing eye wash station with manual and pedal controls.

- Frost-free system as standard
- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- ¼-turn valve, flow activated by hand or pedal controls
- Water supply F1"
- Galvanised steel pipes, green powder-coated basin and controls

Free-standing	9201	£573.72
---------------	------	---------




Single spray eye wash

Trigger-operated single spray eye wash.

- Eye wash spray head fitted with auto-ejecting protective cap
- Trigger-operated, spring automatically shuts off spray
- Flow rate 6 lpm at 3 bar
- Integrated aerator with stainless steel double filter
- Ergonomic grip and trigger in green polypropylene

Wall-mounted	9120C	£141.67
Deck-mounted	9140C	£185.56



Dual spray eye wash

Trigger-operated dual spray eye wash.

- Eye wash spray heads fitted with auto-ejecting protective caps
- Trigger-operated, spring automatically shuts off spray
- Flow rate 9 lpm at 3 bar
- Integrated aerators with stainless steel double filters
- Ergonomic grip and trigger in green polypropylene

Wall-mounted	9121	£155.81
Deck-mounted	9141	£212.30



Safety shower head

Replacement shower head for safety shower.

- Circular shower head Ø 250mm, M1"
- Green shock-resistant ABS
- Flow rate 70 lpm at 1 bar dynamic pressure (120 lpm at 3 bar dynamic pressure)
- Water supply F1"

Shower head	9225	£48.85
-------------	------	--------



Aerator & protective caps

Aerators and protective caps for eye wash stations.

- Aerator F22/100 with grid for comfortable spray
- Protective caps in green, shock-resistant ABS. Eject automatically when eye wash is activated. Supplied in packs of 2

Aerator, hand spray	A22D75	£15.35
Aerator, eye wash	A22LY75	£15.35
Protective caps	91AA75	£6.99

