

DELABIE

WATER SAVINGS  
HYGIENE  
ACCESSIBILITY  
DESIGN

Water controls for public and commercial places  
Accessibility and Independence  
Hygienic accessories for public places  
Stainless steel sanitary ware



More information at [delabie.co.uk](http://delabie.co.uk)



Tel: (01495) 767600 Fax: (01495) 767601 Email: [sales@faucets.co.uk](mailto:sales@faucets.co.uk)

Prices are excluding VAT

## Commercial controls - Basins


**TEMPOMATIC 4**

Electronic mixer or tap with integrated 6V Lithium battery, reduced-stagnation solenoid valve and electronic unit.

- Flow rate pre-set at 3 lpm at 3 bar
- PEX flexibles with filters and non-return valves
- Chrome-plated brass body with reinforced fixings
- Anti-blocking security and temperature limiter
- Duty flush (~60 seconds every 24 hours after the last use)

Deck-mtd mixer Ø 15mm	<b>49000615</b>	<b>£316.00</b>
Deck-mtd tap Ø 15mm	<b>44000615*</b>	<b>£285.04</b>
Wall-mtd tap L. 125 F¾"	<b>443406</b>	<b>£276.73</b>
Wall-mtd tap L. 190 F¾"	<b>443506</b>	<b>£307.70</b>

Stocked\*

**BINOPTIC**

Electronic mixer or tap with infrared presence detection.

- Flow rate pre-set at 3 lpm at 3 bar
- PEX flexibles with filters and Ø 15mm solenoid valves
- Chrome-plated brass body with reinforced fixings
- Anti-blocking security and temperature limiter
- Duty flush (~60 seconds every 24 hours after the last use)
- Independent IP65 electronic control unit and shockproof sensor

Deck-mtd mixer	<b>378MCH15</b>	<b>£408.38</b>
Deck-mtd tap	<b>37801515</b>	<b>£307.61</b>
Wall-mtd tap	<b>379DER15</b>	<b>£314.72</b>
Recessed tap	<b>379ENC15</b>	<b>£322.90</b>

**TEMPOMIX 3**

Time flow mixer with soft-touch operation and temperature control via the push-button.

- Pre-set 7 seconds shut-off delay (adjustable from 3 - 10 seconds)
- Flow rate pre-set at 3 lpm at 3 bar
- PEX flexibles with filters, non-return valves and stopcocks
- Chrome-plated brass body with reinforced fixings
- Vandal resistant and scale-resistant flow straightener


Ø 15mm	<b>79400015</b>	<b>£224.48</b>
F¾"	<b>794000</b>	<b>£218.20</b>

**TEMPOSOFT MIX 2**

Deck-mounted time flow mixer with soft-touch operation.

- Soft-touch operation
- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated brass body with reinforced fixings
- Side temperature control and temperature limiter

Ø 15mm	<b>74250015</b>	<b>£146.36</b>
--------	-----------------	----------------

**TEMPOSOFT 2 tap**

Deck-mounted time flow tap with soft-touch operation.

- Soft-touch operation
- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated brass body

M½"	<b>740500*</b>	<b>£87.36</b>
-----	----------------	---------------


Stocked\*

**TEMPOSOFT 2 wall-mounted**

Wall-mounted tap with soft-touch operation.

- Soft-touch operation
- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Solid brass body M½"

L. 110mm	<b>741500</b>	<b>£61.24</b>
L. 150mm	<b>741550</b>	<b>£73.78</b>

**TEMPOSTOP cross wall kit**

Vandal-resistant time flow tap for cross wall installation.

- Vandal resistant cross wall control and spout for walls ≤ 200mm
- Time flow ~7 seconds, M½" inlet
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Solid brass body
- Anti-blocking system
- Fixed via anti-rotating pin and back-nut

Note: other spouts available on request

With anti-blocking	<b>741943</b>	<b>£164.80</b>
--------------------	---------------	----------------

**TEMPOSTOP**

Deck-mounted time flow tap.

- Time flow ~7 seconds
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Chrome-plated solid brass body with spout H. 35mm, L. 110mm
- Vandal resistant and scale resistant flow straightener

15mm	<b>745250*</b>	<b>£63.08</b>
M½", reinf. fixing	<b>745300</b>	<b>£64.41</b>
M½", anti-blocking	<b>745301</b>	<b>£67.67</b>
15mm, anti-blocking	<b>745351*</b>	<b>£74.12</b>
15mm lever-op	<b>745450</b>	<b>£84.52</b>

Stocked\*



Commercial controls - Showers



**SECURITHERM electronic**

Aluminium epoxy-coated thermostatic battery-operated shower panel for wall-mounted installation.

- SECURITHERM thermostatic mixer
- 6V Battery-operated infrared sensor
- Anti-scalding hot water safety
- Pre-set maximum temperature limiter
- Shuts off on demand or automatically after ~60 seconds
- ROUND, tamperproof shower head with scale-resistant nozzle, 6 lpm at 3 bar
- Integrated stopcocks, filters and non-return valves
- Thermal shocks are possible

With top inlets Ø 15mm	<b>79240015</b>	<b>£771.87</b>
------------------------	-----------------	----------------



**SECURITHERM time flow**

Aluminium epoxy-coated shower panel for wall-mounted installation.

- SECURITHERM thermostatic mixer
- Time flow ~30 seconds
- Soft-touch operation
- Anti-scalding hot water safety
- Pre-set maximum temperature limiter
- ROUND, tamperproof shower head with scale-resistant nozzle, 6 lpm at 3 bar
- Integrated stopcocks, filters and non-return valves
- Thermal shocks are possible

With top inlets Ø 15mm	<b>79230015</b>	<b>£629.81</b>
------------------------	-----------------	----------------



**TEMPOMIX time flow**

Aluminium epoxy-coated shower panel for wall-mounted installation.

- TEMPOMIX time flow mixer ~30 seconds with soft-touch operation
- ROUND, tamperproof shower head with scale-resistant nozzle, 6 lpm at 3 bar
- Ø 15mm connections with integrated stopcocks, filters and non-return valves

With top inlets	<b>79030015</b>	<b>£535.09</b>
-----------------	-----------------	----------------



**SPORTING 2 shower panel**

Anodised aluminium shower panel with adjustable connector for top or back inlets.

- Time flow ~30 seconds
- Tamperproof fixed shower head with scale-resistant nozzle, 6 lpm at 3 bar
- Soft-touch with soft-touch operation
- Integrated stopcock, filter and non-return valve
- M<sup>1</sup>/<sub>2</sub>" connection for mixed water supply

With top/back inlet	<b>714700*</b>	<b>£181.17</b>
---------------------	----------------	----------------

Stocked\*

Commercial controls - Hands free




**TEMPOSTOP**

Time flow shower valve for exposed or recessed installation.

- Time flow valve ~15 or 30 seconds
- Flow rate 12 lpm at 3 bar, can be adjusted (9 lpm for exposed model)
- F<sup>1</sup>/<sub>2</sub>" or Ø 15mm connections
- Solid brass body, recessed model features stainless steel wall plate Ø 130mm or 160 × 160mm

Recessed Ø 130mm, F <sup>1</sup> / <sub>2</sub> ", 30 sec	<b>749128</b>	<b>£107.87</b>
Recessed 160 × 160mm, F <sup>1</sup> / <sub>2</sub> ", 30 sec	<b>749628</b>	<b>£107.87</b>
Exposed, Ø 15mm, 15 sec	<b>74972515</b>	<b>£100.87</b>



**TEMPOSTOP**

Time flow cross wall shower kit.

- Time flow ~15 or 30 seconds
- Vandal resistant cross wall control
- ROUND shower head with tamperproof and scale-resistant nozzle
- Flow rate set at 6 lpm at 3 bar
- Solid brass body
- Concealed fixings and anti-rotating nut

For walls ≤ 150mm	<b>749159</b>	<b>£213.34</b>
For walls ≤ 200mm, AB	<b>747214</b>	<b>£207.20</b>




**TEMPOGENOU**

Knee-operated time flow valve for hands-free operation.

- Time flow ~7 seconds and pre-set flow rate 3 lpm
- Control lever reinforced by stainless steel rod
- Wall plate mounted via 4 stainless steel screws
- Cold or mixed water supply

MM <sup>1</sup> / <sub>2</sub> ", inline	<b>73544715</b>	<b>£110.92</b>
MM <sup>1</sup> / <sub>2</sub> ", angled	<b>734100</b>	<b>£87.26</b>



**Deck-mounted spout**


Fixed cast brass spout for hands-free operation.

- Spout L. 140mm, H. 120mm, M<sup>1</sup>/<sub>2</sub>"
- Reinforced fixing via 3 stainless steel screws
- Chrome-plated solid brass body
- Flow straightener set at 3 lpm at 3 bar

Deck-mounted	<b>981142</b>	<b>£71.63</b>
--------------	---------------	---------------



## Commercial controls - WCs

**TEMPOMATIC WC**

Cross wall electronic direct flush valve for WCs.

- IP65 independent electronic unit
- Mains supply with 1" solenoid valve
- On demand or automatic flush
- Time flow ~7 seconds, can be adjusted from 3-12 seconds
- Detection distance, flow rate and flush volume can be adjusted
- Stopcock, connection washer and vacuum breaker

For walls ≤ 30mm	<b>463030</b>	<b>£699.68</b>
For walls ≤ 160mm	<b>463150</b>	<b>£699.68</b>
For walls ≤ 225mm	<b>463200</b>	<b>£705.09</b>

**TEMPOFLUX 1 WC**

Time flow direct flush valve with soft-touch operation for WCs.

- Time flow ~7 seconds
- Chrome-plated solid brass body
- Integrated vacuum breaker


With stopcock	<b>761001</b>	<b>£120.42</b>
Without stopcock	<b>761000</b>	<b>£81.16</b>

**TEMPOFLUX 2 WC**

Time flow direct flush valve for WCs.

- Chrome-plated push-button and solid brass body
- Integrated stopcock and flow rate/flush volume adjuster
- Integrated vacuum breaker
- Inlet M<sup>3</sup>/<sub>4</sub>" and outlet connection for PVC tube Ø 26/32mm
- Recessing depth can be adjusted from 0-20mm for ref.s 762902 & 762901

3L/6L recessed	<b>762902</b>	<b>£207.82</b>
3L/6L cross wall	<b>762150</b>	<b>£185.70</b>
6L recessed	<b>762901</b>	<b>£191.69</b>

**TEMPOFLUX 1 WC cross wall kit**

Cross wall time flow direct flush kit with soft-touch operation for WCs.

- Cross wall control, can be cut to size
- Inlet M<sup>3</sup>/<sub>4</sub>" with integrated stopcock and flow rate/flush volume adjuster
- Integrated vacuum breaker
- Cross wall control, can be cut to size
- Connection washer Ø 32/55mm

≤ 150mm, with flush tube	<b>761700</b>	<b>£196.63</b>
≤ 200mm, without flush tube	<b>761200</b>	<b>£168.31</b>

## Commercial controls - Urinals

**TEMPOMATIC 4 urinal exposed**

Electronic valve with integrated 6V Lithium battery, reduced-stagnation solenoid valve and electronic unit.

- High frequency mode, active during busy periods
- 3 rinsing programmes
- Hygienic duty flush every 24 hours after last use
- Integrated stopcock and flow rate 0.25 l/sec at 3 bar, can be adjusted
- One-piece chrome-plated metal body M<sup>1</sup>/<sub>2</sub>"

Inline	<b>479406</b>	<b>£310.46</b>
Angled	<b>479408</b>	<b>£277.18</b>
Angled, flush tube Ø 35mm	<b>479407</b>	<b>£299.37</b>

**TEMPOMATIC 4 urinal recessed**

Electronic valve for waterproof, recessed individual urinals.

- Mains supply or battery operated
- Stainless steel wall plate 145 × 145mm with integrated electronics
- High frequency mode
- 3 rinsing programmes
- Hygienic duty flush every 12 or 24 hours (or off)
- Waterproof housing, for all installation types

Note: satin finish also available


Polished st. steel 6V battery	<b>430PBOX + 430016</b>	<b>£100.18</b>	<b>£294.14</b>
Polished st. steel Mains	<b>430SBOX + 430010</b>	<b>£101.25</b>	<b>£314.40</b>

**TEMPOSOFT 2 urinal recessed**

Time flow recessed urinal valve with soft-touch operation for standard or siphon action urinals.

- Bright polished stainless steel wall plate Ø 130mm on recessed model
- Flow rate pre-set at 0.15 l/sec at 3 bar, can be adjusted
- Soft-touch operation
- Time flow ~3 seconds
- Solid brass valve body M<sup>1</sup>/<sub>2</sub>"

Recessed	<b>777130</b>	<b>£87.41</b>
For panels	<b>777140</b>	<b>£68.67</b>

**TEMPOSOFT 2 urinal exposed**

Time flow exposed urinal valve with soft-touch operation for standard or siphon action urinals.

- Bright polished stainless steel wall plate and solid brass body
- Flow rate pre-set at 0.15 l/sec at 3 bar, can be adjusted
- Soft-touch operation
- Time flow ~3 seconds
- Solid brass valve body M<sup>1</sup>/<sub>2</sub>"

Inline	<b>777800</b>	<b>£59.13</b>
Angled	<b>778800</b>	<b>£56.56</b>



## Frame systems



### TEMPOFIX 3 with TEMPOMATIC 4 urinal

Frame system W. 420mm with electronic urinal valve.

- Frame system in black epoxy coated steel with wall fixings
- Fixes to load-bearing floors and walls
- Frame height can be adjusted
- Bracket can be adjusted
- Conforms to French standard NF D12-208
- For walls up to 120mm
- Features TEMPOMATIC 4 electronic valve F1½"
- Uses 6V Lithium batteries
- For urinal valves Ø 35mm

Also available with mains supply

Bright stainless steel finish	543006 + 430016	£341.04 £294.14
Satin stainless steel finish	543006 + 430006	£341.04 £294.14



### TEMPOFIX 3 with TEMPOSTOP urinal

Frame system W. 420mm with time flow urinal valve.

- Frame system in black epoxy coated steel with wall fixings
- Fixes to load-bearing floors and walls
- Frame height can be adjusted
- Bracket can be adjusted
- Conforms to French standard NF D12-208
- Features TEMPOSTOP M1½" time flow direct flush valve
- Time flow ~3 seconds

For walls 20 - 40mm	538400	£404.98
For walls 40 - 130mm	538450	£420.98




### TEMPOFIX 3 with TEMPOMATIC WC

Frame system W. 350mm with electronic WC valve.

- Frame system in black epoxy coated steel
- Fixes to load-bearing floors or walls
- Frame height can be adjusted
- Soil pipe Ø 100mm
- Conforms to French standard NF D12-208
- For drywalls 26 - 70mm
- Features TEMPOMATIC electronic direct flush valve F1"
- 230/12V transformer

Free-standing model	547005	£751.35
	+ 546412	£251.52
Wall-mounted model	547000	£740.70
	+ 546412	£251.52



### TEMPOFIX 3 with TEMPOFLUX 2 WC

Frame system W. 350mm with time flow WC valve.

- Free-standing frame system in black epoxy coated steel
- Fixes to load-bearing floors, with large feet
- Frame height can be adjusted from 0-200mm
- Soil pipe Ø 100mm
- Conforms to French standard NF D12-208
- Features TEMPOFLUX 2 time flow direct flush valve M¾"

Also available with wall fixings and for other wall thicknesses

Dual flush 3L/6L For walls 20-40mm	578305 + 578222	£357.03 £82.06
Single flush 6L For walls 20-40mm	578300 + 578212	£341.04 £74.60

## Additional Fittings



### PREMIX NANO

TMV3 approved point-of-use thermostatic mixing valve for 1 - 2 basins or 1 shower.

- Anti-scalding safety: immediate shut-off if cold or hot water supply fails
- Temperature pre-set at 38°C, can be adjusted from 34 - 60°C
- Thermal shocks at 85°C are possible
- Integrated filters and non-return valves

M1½" 15mm, chrome	732116*	£75.57
M1½" 15mm, nickel	732115	£64.22

Stocked\*



### PREMIX COMFORT

Group thermostatic mixing valve for mixed water distribution.

- Anti-scalding safety: maximum temperature limiter
- Temperature pre-set at 38°C, can be adjusted from 32 - 42°C
- Thermal shocks at 85°C are possible
- Integrated non-return valves and filters can be accessed externally
- For up to 40 points-of-use, flow rate 55 - 190 lpm at 3 bar

¾", 55 lpm	731002	£432.70
1", 90 lpm	731003	£670.69
1¼", 140 lpm	731004	£962.76
1½", 190 lpm	731005	£1,243.98



### Adjustable height floor trap

Floor trap for soft or vinyl floors with adjustable height.

- Flow rate 36 lpm, outlet Ø 43mm
- Water level 50mm
- Polished stainless steel grid Ø 114mm
- Integrated plate to seal waterproof membrane
- Height adjusts up to 85mm with extension

Outlet Ø 43 mm	683002UK*	£53.20
----------------	-----------	--------

Stocked\*



### BIOSAFE spout outlet


Hygienic spout outlet for mixers and taps.

- Free flow outlet with no grid or partitions in contact with the water
- Water cannot stagnate in the internal parts
- Scale-resistant Hostaform® interior
- Chrome-plated brass collar
- Flow rate must be limited to ensure a smooth, laminar flow

M24/100	923024	£5.55
F22/100	923022	£5.55




## Hospital

**Electronic mixer**

Electronic mixer with swivelling spout. Smooth body and spout interiors.

- Infrared sensor and temperature control via control lever L. 100mm
- Mains supply 230/12V or 6V Lithium battery-operated
- Flow rate pre-set at 3 lpm at 3 bar, can be adjusted from 1.5 - 6 lpm
- Duty flush (~60 seconds every 24 hours after the last use)

H. 165 L. 160	<b>20164T115</b>	<b>£504.94</b>
H. 305 L. 250	<b>20164T415</b>	<b>£543.37</b>
H. 165 L. 160, 6V	<b>20464T115</b>	<b>£666.09</b>
H. 305 L. 250, 6V	<b>20464T415</b>	<b>£687.40</b>

**Electronic mixer BIOCLIP spout**

Electronic mixer with BIOCLIP removable spout. Smooth body and spout interiors.

- BIOCLIP spout can be removed for cleaning and disinfection
- Infrared sensor and temperature control via control lever L. 100mm
- Mains supply 230/12V
- Flow rate limited to 7 lpm at 3 bar
- Duty flush (~60 seconds every 24 hours after the last use)
- Suitable for BIOFIL spouts


Spout H. 160	<b>20870T115</b>	<b>£570.83</b>
Spout H. 300	<b>20870T315</b>	<b>£592.79</b>

**Mechanical mixer BIOCLIP spout**

Mixer with BIOCLIP removable spout and Hygiene lever. Smooth body and spout interiors.

- BIOCLIP spout can be removed for cleaning and disinfection
- Ceramic cartridge Ø 40mm with maximum temperature limiter
- Flow rate limited to 5 lpm at 3 bar
- Suitable for BIOFIL spouts


Spout H. 160	<b>2870T1</b>	<b>£277.83</b>
Spout H. 300	<b>2870T3</b>	<b>£299.79</b>

**BIOSAFE mechanical mixer**

Mechanical mixer with no spout and Securitouch thermal insulation to prevent burns.

- BIOSAFE hygienic spout outlet integrated into the body
- Smooth interior and very low water volume
- Flow rate limited to 4 lpm at 3 bar
- Thermal shocks are possible
- Available with Pressure Balancing (EP)
- Copper tails

With waste	<b>26206</b>	<b>£140.69</b>
No waste	<b>26216</b>	<b>£119.37</b>
EP, with waste	<b>26206EP</b>	<b>£172.66</b>
EP, no waste	<b>26216EP</b>	<b>£151.34</b>

**SECURITHERM sequential mixer**

Single control thermostatic mixer. TMV3 approved.

- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- Smooth interior slows bacterial development
- No non-return valves

15mm, lever L. 146	<b>H960015</b>	<b>£281.19</b>
15mm, lever L. 100	<b>H960015L</b>	<b>£278.46</b>
Coppertails, lever L. 146	<b>H9600610</b>	<b>£305.01</b>
Coppertails, lever L. 100	<b>H9600610L</b>	<b>£307.80</b>

**SECURITHERM sequential BIOCLIP mixer**

Removable single control thermostatic BIOCLIP mixer. TMV3 approved.

- Mixer can be easily removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- Smooth interior slows bacterial development
- No non-return valves

15mm, lever L. 146	<b>H960515</b>	<b>£324.45</b>
15mm, lever L. 100	<b>H960515L</b>	<b>£321.30</b>
Coppertails, lever L. 146	<b>H9605610*</b>	<b>£360.80</b>
Coppertails, lever L. 100	<b>H9605610L</b>	<b>£354.90</b>

Stocked\*

**Wall-mtd SECURITHERM BIOCLIP mixer**

Single control thermostatic mixer with BIOCLIP spout. TMV3 approved.

- BIOCLIP spout can be removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves
- Smooth interior slows bacterial development

150mm, inline SP	<b>H9611P</b>	<b>£400.20</b>
200mm, inline SP	<b>H9614P*</b>	<b>£399.46</b>

Stocked\*

**Pillar-mtd SECURITHERM BIOCLIP mixer**

Single control thermostatic mixer with BIOCLIP spout. TMV3 approved.

- BIOCLIP spout can be removed for cleaning and disinfection
- Progressive temperature control from cold water to 40°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Flow rate regulated at 7 lpm
- No non-return valves
- Smooth interior slows bacterial development

200mm, pillar	<b>H9615</b>	<b>£455.22</b>
---------------	--------------	----------------



Tel: (01495) 767600 Fax: (01495) 767601 Email: sales@faucets.co.uk

Prices are excluding VAT

Hospital



**BIOFIL cartridge filter**

Single use BIOFIL cartridge with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Maximum duration 62 days for both non-sterile and sterile filter
- 10 cartridges individually wrapped

Sterile	20050A.10P	£655.95
Sterile	20050P.10P	£655.95
Non-sterile	30050A.10P	£523.71
Non-sterile	30050P.10P	£523.71
Connector 'A' F22/100	820022	£15.83
Connector 'A' M24/100	820024	£15.83
Connector 'P' F22/100	820122	£20.26
Connector 'P' M24/100	820124	£20.26



**BIOFIL shower head filter**

Single use BIOFIL shower head with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Maximum duration 62 days for both non-sterile and sterile filter
- 10 shower heads individually wrapped

Sterile threaded	20061.10P	£823.34
Non-sterile threaded	30061.10P	£690.81
Sterile push-fit	20060.10P	£823.34
Non-sterile push-fit	30060.10P	£690.81



**BIOFIL spout filter**

Single use BIOFIL spout with integrated filter.

- Immediate protection against waterborne nosocomial infection
- Sterilising grade 0.1 micron absolute-rated
- Maximum duration 62 days for both non-sterile and sterile filter
- 10 spouts individually wrapped

Sterile	20040A.10P	£678.57
Non-sterile	30040A.10P	£668.53



**BIOCLIP spouts**

Removable BIOCLIP spouts in stainless steel and Hostaform®.

- For use with BIOCLIP mixers/taps
- Removable stainless steel spouts Ø 28mm with hygienic flow straightener suitable for BIOFIL terminal filters. Available in two lengths, 129mm and 77mm
- Disposable Hostaform® spouts Ø 22mm with star-shaped flow straightener. Length 125mm. Individually wrapped

2 × St. steel, L. 129	20002	£69.89
2 × St. steel, L. 77	20003	£62.69
15 × Hostaform®, L. 125	20015	£69.48



**SECURITHERM Securitouch sequential shower**

Single control thermostatic shower mixer.

- Progressive temperature control from cold water to 39°C
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Thermostatic sequential cartridge Ø 40mm with maximum temperature limiter
- Smooth interior slows bacterial development
- Flow rate regulated at 9 lpm
- 150mm centres with fast fix connectors supplied

M½" bottom outlet	H963015	£270.04
M¾" top outlet	H964015	£270.04



**SECURITHERM Securitouch shower**

Dual control thermostatic shower mixer.

- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Securitouch thermal insulation prevents burns
- Adjustable temperature 25 - 41°C with maximum temperature limiter
- M½" outlet
- 150mm in-line connectors with filters and non-return valves
- Supplied with in-line STOP/PURGE connectors

M½"	H9741TP	£244.28
-----	---------	---------



**SECURITHERM sequential recessed shower**

Single control thermostatic shower mixer in a waterproof housing.

- Sequential shower with polished stainless steel cover plate
- Securitouch thermal insulation prevents burns
- Anti-scalding failsafe: shuts off immediately if cold water supply fails
- Maximum temperature limiter
- Thermal shocks are possible
- Flow rate regulated at 9 lpm

SECURITHERM shower	H9632*	£267.96
Waterproof housing	790BOX*	£75.56

Stocked\*



**SECURITHERM EP Securitouch shower**

Pressure-balancing shower mixer.

- Securitouch thermal insulation prevents burns
- EP pressure-balancing ceramic cartridge Ø 40mm with maximum temperature limiter
- M½" outlet with flow rate regulated at 9 lpm
- M½" M¾" offset connectors with filters and non-return valves

With STOP/PURGE unions	2739EP	£241.19
------------------------	--------	---------



## Accessibility &amp; Independence

**DOC M recessed shower pack**

DOC M compliant white epoxy coated shower pack.

- 2 × drop-down bars, 3 × 600mm grab bars, 2 × 450mm grab bars
- Lift-up shower seat with backrest
- White PVC shower curtain and rail
- SECURITHERM thermostatic recessed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and wall outlet
- Stainless steel coat hook

White epoxy	DOCMREC1	£1,552.37
-------------	----------	-----------

**DOC M recessed shower pack**

DOC M compliant blue epoxy coated shower pack.

- 2 × drop-down bars, 3 × 600mm grab bars, 2 × 450mm grab bars
- Lift-up shower seat with backrest
- White PVC shower curtain and rail
- SECURITHERM thermostatic recessed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and wall outlet
- Stainless steel coat hook

Blue epoxy	DOCMREC2	£1,552.37
------------	----------	-----------

**DOC M exposed shower pack**

DOC M compliant white epoxy coated shower pack.

- 2 × drop-down bars, 3 × 600mm grab bars, 2 × 450mm grab bars
- Lift-up shower seat with backrest
- White PVC shower curtain and rail
- SECURITHERM thermostatic exposed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and 1.0m riser pipe
- Stainless steel coat hook

White epoxy	DOCMEXP1	£1,398.79
-------------	----------	-----------

**DOC M exposed shower pack**

DOC M compliant blue epoxy coated shower pack.

- 2 × drop-down bars, 3 × 600mm grab bars, 2 × 450mm grab bars
- Lift-up shower seat with backrest
- White PVC shower curtain and rail
- SECURITHERM thermostatic exposed shower mixer and diverter
- TONIC JET shower head regulated at 6 lpm
- Multimode shower kit, 1.5m hose with retaining collar and 1.0m riser pipe
- Stainless steel coat hook

Blue epoxy	DOCMEXP2	£1,398.79
------------	----------	-----------

## Accessibility &amp; Independence

**Basic straight grab bar**

Grab bar in 304 stainless steel with satin finish.

- Concealed fixings
- Ø 32mm
- Maximum recommended user weight: 135 kg
- 10 year warranty. CE marked

300mm	35050S	£34.75
400mm	350504S	£38.63
500mm	350505S	£42.10
600mm	350506S	£46.67

**Basic drop-down grab bar**

Drop-down grab bar in 304 stainless steel with satin finish.

- Length 850mm
- Ø 32mm
- Maximum recommended user weight: 135 kg
- 10 year warranty. CE marked
- Tube thickness: 1.2mm

850mm	35164S	£152.69
-------	--------	---------

## Hygienic Accessories

**Electronic soap dispenser**

Wall-mounted stainless steel liquid soap dispenser.

- Non-touch, zero waste pump dispenser, 0.8ml. dose
- Power supply: 6 AA batteries included
- Capacity: 0.65 litres
- For vegetable-based liquid soap (up to 3,000 mPa.s)
- Window allows soap level to be checked

Electronic	510587	£109.93
------------	--------	---------

**Liquid soap dispenser**

Liquid soap dispenser with soft-touch operation .

- 304 Stainless steel
- One-piece hinged cover is easy to clean and maintain
- Anti-blocking system and no-waste pump dispenser
- Lock and level control
- For vegetable-based liquid soap (up to 3,000 mPa.s)

1L, bright polished	510580	£85.04
1L, polished satin	510582	£79.63
1L, white epoxy	510581	£69.41
0.5L, bright polished	510583	£79.95
0.5L, polished satin	510586	£74.84
0.5L, white epoxy	510584	£65.24



Tel: (01495) 767600 Fax: (01495) 767601 Email: sales@faucets.co.uk

Prices are excluding VAT



## Sanitary Ware



### BOB washbasin

Wall-mounted stainless steel washbasin with concealed drainage.

- Basin internal diameter 310mm
- Bacteriostatic 304 stainless steel, 1.2mm thick
- Polished satin finish
- Rounded edges prevent injury
- Vandal-resistant shrouded basin, concealed trap
- Supplied with 1½" waste and trap, no overflow
- Complies with EN 14688

Without tap hole	<b>120130</b>	<b>£261.89</b>
------------------	---------------	----------------



### FRAJU washbasin

Wall-mounted stainless steel washbasin.

- Overall size 540 × 480mm
- Bacteriostatic 304 stainless steel, 1.2mm for bowl, 1.5mm for surround
- Polished satin finish
- Rounded edges prevent injury
- Supplied with 1¼" waste, no overflow
- Complies with EN 14688

Without tap hole	<b>120430</b>	<b>£275.62</b>
Tap hole Ø 35mm	<b>121430</b>	<b>£275.62</b>



### CANAL wash trough

Wall-mounted stainless steel wash trough for 1 - 5 services.

- Bacteriostatic 304 stainless steel, 1mm for bowl, 1.5mm for surround
- Polished satin finish
- Light weight, easy to install (no joint concealers)
- Supplied with brackets and fixing elements
- Complies with EN 14296

L 600, 1 service	<b>120240</b>	<b>£307.48</b>
L 1,200, 2 services	<b>120250</b>	<b>£373.43</b>
L 1,200, with tap hole	<b>121250</b>	<b>£373.43</b>
L 1,400, 2-3 services	<b>120260</b>	<b>£402.56</b>
L 1,800, 3-4 services	<b>120280</b>	<b>£461.71</b>
L 2,400, 4 services	<b>120300</b>	<b>£529.61</b>
L 3,000, 5 services	<b>120310</b>	<b>£583.93</b>



### SD drinking fountain

Wall-mounted stainless steel drinking fountain.

- Bacteriostatic 304 stainless steel, 1.5mm thick
- Polished satin finish
- Rounded edges prevent injury
- Supplied with WRAS approved chrome-plated time flow bubbler tap, M¾"
- Vandal-resistant, flat perforated waste, outlet 1¼"
- Weight 2.4kg. Supplied with fixing elements

With bubbler	<b>180800</b>	<b>£311.19</b>
--------------	---------------	----------------



### S21 and 700 WC pans

Wall-hung or floor-standing stainless steel WC pans.

- Bacteriostatic 304 stainless steel, 1.5mm thick
- Polished satin finish
- One-piece pressed bowl with no seams
- Concealed perimetral flushing rim
- Horizontal inlet Ø 55mm; horizontal waste Ø 100mm. Supplied with PVC pipe
- Easy to install

S21 S wall-hung	<b>110310</b>	<b>£662.22</b>
S21 P floor-mtd	<b>110300</b>	<b>£659.20</b>
700 S wall-hung	<b>110710</b>	<b>£847.99</b>
700 P floor-mtd	<b>110700</b>	<b>£725.12</b>



### Trough urinal

Wall-hung stainless steel trough urinal

- Bacteriostatic 304 stainless steel, 1.2mm thick
- Polished satin finish
- Top inlet M½" and sparge pipe for rinsing
- 1½" waste outlet, drains on the right side
- Weight: 1,200mm model is 15.4kg, 1,800mm model is 22.1kg, 2,400mm model is 28.5kg
- Siphon not included

L 1,200mm	<b>130100</b>	<b>£491.46</b>
L 1,800mm	<b>130110</b>	<b>£569.40</b>
L 2,400mm	<b>130120</b>	<b>£738.25</b>



### MINERALCAST wash trough

Wall-mounted wash trough available with 2 or 3 services.

- Natural minerals and polyester resin composite
- Uniform, non-porous surface
- One-piece cast washbasin with no seams
- Central tap hole Ø 35mm
- Supplied with 1½" waste, no overflow

L 1,200mm, 2 services	<b>454122</b>	<b>£940.87</b>
L 1,800mm, 3 services	<b>454182</b>	<b>£1,217.32</b>



### MINERALCAST wash trough

Wall-mounted wash trough with 3 services.

- Natural minerals and polyester resin composite
- Uniform, non-porous surface, ideal for schools
- One-piece cast washbasin with no seams
- With incline to prevent pooling
- Supplied with 1¼" waste, no overflow

L 1,400mm, 3 services	<b>453140</b>	<b>£1,299.76</b>
-----------------------	---------------	------------------



## Safety Controls



### Eye wash and shower combination

Free-standing safety eye wash and shower with large flow rates.

- Frost-free system as standard
- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- Circular shower head Ø 250mm, flow rate 120 lpm at 3 bar
- Galvanised steel pipes, green epoxy-coated controls

Combination	<b>9203</b>	<b>£768.88</b>
-------------	-------------	----------------



### Wall-mounted safety shower

Recessed safety shower with manual control.

- Frost-free system as standard
- Circular shower head Ø 250mm, flow rate 120 lpm at 3 bar
- ¼-turn valve operated by triangular handle
- Water supply F1"
- Galvanised steel pipes, green epoxy-coated shower head and handle

Shower	<b>9108</b>	<b>£158.45</b>
--------	-------------	----------------



### Wall-mounted eye wash station

Wall-mounted eye wash station with manual control.

- Frost-free system as standard
- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- ¼-turn valve, flow activated by hand control
- Water supply M½"
- Galvanised steel pipes, green epoxy-coated bowl and control

Wall-mounted	<b>9102</b>	<b>£323.07</b>
--------------	-------------	----------------



### Free-standing eye wash station

Free-standing eye wash station with manual and pedal controls.

- Frost-free system as standard
- 304 stainless steel basin Ø 250mm, flow rate 20 lpm at 3 bar
- Eye wash spray heads fitted with auto-ejecting protective caps
- ¼-turn valve, flow activated by hand or pedal controls
- Water supply F1"
- Galvanised steel pipes, green epoxy-coated bowl and controls

Free-standing	<b>9201</b>	<b>£523.37</b>
---------------	-------------	----------------




### Single spray eye wash

Trigger-operated single spray eye wash.

- Eye wash spray head fitted with auto-ejecting protective cap
- Trigger-operated, spring automatically shuts-off spray
- Flow rate 16 lpm at 3 bar
- Integrated aerator with stainless steel double filter
- Ergonomic grip and trigger in green polypropylene

Wall-mounted	<b>9120C</b>	<b>£129.25</b>
Deck-mounted	<b>9140C</b>	<b>£169.27</b>



### Dual spray eye wash

Trigger-operated dual spray eye wash.

- Eye wash spray heads fitted with auto-ejecting protective caps
- Trigger-operated, spring automatically shuts-off spray
- Flow rate 15 lpm at 3 bar
- Integrated aerator with stainless steel double filter
- Ergonomic grip and trigger in green polypropylene

Wall-mounted	<b>9121</b>	<b>£142.13</b>
Deck-mounted	<b>9141</b>	<b>£193.66</b>



### Safety shower head

Replacement shower head for safety shower.

- Circular shower head Ø 250mm, M1"
- Green shockproof ABS
- Flow rate 70 lpm at 1 bar (120 lpm at 3 bar)
- Water supply F1"

Shower head	<b>9225</b>	<b>£44.56</b>
-------------	-------------	---------------



### Aerator & protective caps

Replacement aerators and protective cap for eye wash stations.

- **Aerator** F22/100 with grid for comfortable spray
- **Protective caps** in green, shockproof ABS  
Eject automatically when eye wash is activated
- Supplied in packs of 2

Aerator, hand spray	<b>A22D75</b>	<b>£14.01</b>
Aerator, eye wash	<b>A22LY75</b>	<b>£14.01</b>
Protective caps	<b>91AA75</b>	<b>£6.37</b>